

Motorcycle Manufacturer	MBK
Model	KILIBRE 300
Issue	05/03 Rev. 00


This model is pre-wired for the connection of a security system.


Recommended siting of the alarm unit	Under the front shield, behind the headlamp.	
Position of the o.e. plugs for	Under the front shield, fastened to the harness that is	
the connection of an alarm	connected to the cigarette-lighter receptacle.	
Connection	Follow the instructions herebelow. The plugs are	
	viewed from the wire side.	



White connector

Position	Function	Connect to alarm wire
1	Positive power supply +12V	Red
2	Ignition controlled positive supply +15	Orange
3	Negative power supply	Black





Black connector

Position	Function	Connect to alarm wire
1	Left turn indicator	Yellow
2	Right turn indicator	Yellow



White connector + jumper

Position	Function	Connect to alarm wire
1	Engine immobiliser	Violet
2	Engine immobiliser	Brown

The information contained herein is merely indicative and without responsibility on SPYBALL. You are strongly recommended to check for possible discrepancies or for changes made by the motorcycle manufacturer prior to connecting. COBRA AUTOMOTIVE TECHNOLOGIES SPA - SPYBALL BUSINESS UNIT - VIA ASTICO 41 – 21100 VARESE (VA) www.spyball.it technical@spyball.it